




SECTION A-A




FRONT VIEW




SECTION B-B




DETAIL A




mounting on concrete or light weight concrete



mounting on brick wall



mounting on insulated cladding



NOTE: - The mounting surfaces for the dock shelters must be levelled and in line.

WORK TO BE CARRIED OUT BY CUSTOMER, UNLESS IN ADVANCE OTHERWISE IS AGREED IN WRITING.

Constructional :

- Supply necessary mounting surface and free room as shown.

- NECESSARY MOUNTING SURFACE
- NECESSARY FREE SIDE ROOM

YOUR DIMENSIONS :		OW	OH	PD	W	H	FS
ITEM :	TYP :						
ITEM :	TYP :						
ITEM :	TYP :						
Wall structure :	(1-3) <input type="checkbox"/>	otherwise :					

UNITS in mm	
OW =	Overall width
OH =	Tallest truck plus 500mm minimal
PD =	Projection depth
W =	Door width
H =	Door height
FS =	Free side room = min.50



Customer :	Quotation No :
Project :	No :
Architect :	Date of issue :
Your Ref. No :	
Scale:	Tolerance: -0/+10
Doc. No: 403M.003IAF	Rev.: 22-04-2011

INSTALLATION DRAWING
DOCK SHELTER