

KÕRGELE TÕSTVAD TÕSTUKID

	Kirjeldus MUDEL	Tõstejõud (Kg)	Platvorm (L x W) (mm)	Alusraam (L x W) (mm)	Max pikkus laiendus (mm)	Max pikkus kal. kaitsega (mm)	Max laius laiendus (mm)	Tõste kõrgus (mm)	Suletud kõrgus (mm)	Tõste aeg (sec)	Mootor (kW)	Kaal (kg)
860660	JXY0-4/80-1C	400	800 x 600	700 x 600	1150		850	800	200	19	0,55	120
860105	x JXY2-5/180-1C**	500	1350 x 1000	1350 x 850	1700	1900	1200	1800	350	21	2,2	450
860102	JXY2-5/320-2C	500	2250 x 1000	2250 x 850	2600	2800	1500	3200	400	36	2,2	650
860110	x JXY2-10/180-2C	1000	1350 x 1000	1350 x 850	1700	1850	1500	1800	350	21	2,2	450
860114	JXY2-10/200-2C	1000	1500 x 1000	1500 x 850	1850	2150	1500	2000	350	21	2,2	490
860115	JXY2-10/250-2C	1000	1800 x 1000	1800 x 850	2150	2350	1500	2500	350	30	2,2	540
860118	JXY3-10/320-2C	1000	2250 x 1000	2250 x 850	2600	2800	1500	3200	500	43	2,2	870
860180	x JXY2-10/330-2C*	1000	1650 x 1200	1650 x 1000	1950	2100	1700	3300	530	34	2,2	665
860111	JXY2-15/180-2C	1500	1350 x 1000	1350 x 850	1600	1700	1500	1800	400	21	2,2	450
860120	JXY3-20/200-2C	2000	1500 x 1000	1500 x 850	1900	2100	1500	2000	500	25	2,2	645
860121	JXY3-20/200-2C	2000	1500 x 1800	1500 x 1560	1900	2100	2000	2000	500	40	2,2	900
860123	JXY3-20/320-2C	2000	2250 x 1000	2250 x 850	2650	2800	1500	3200	530	40	4,0	870
860190	JXY3-20/380-2C*	2000	2250 x 1200	2250 x 1050	2600	2800	1700	3800	800	41	4,0	1150
860124	JXY3-20/380-2C*	2000	2250 x 1800	2250 x 1560	2600	2800	2000	3800	800	41	4,6	1250
860125	JXY3-20/430-2C	2000	3000 x 1200	3000 x 1050	3300	3300	1700	4300	650	43	4,0	1140
860126	JXY3,5-25/320-2C	2500	2500 x 1200	2500 x 1060	2800	3000	1800	3200	530	40	4,6	1350
860130	JXY4-30/300-2C	3000	2500 x 1300	2250 x 1150	2900	3100	1800	3000	700	33	4,0	1580
860140	JXY4-40/300-2C	4000	2500 x 1500	2250 x 1350	2900	3100	2000	3000	700	46	4,0	1650

Kõik mudelid (va. 860660) on eraldi asetseva "power-pack"-iga

** MÄRKUS! Mudelit 860105 võib kasutada 1000 kg koormusega, kuid ainult platvormi standardmõõtude korral!